

LIGHT DUTY PORTABLE LIFTS

1,000/2,000/4,000 LBS

LIFT & TILTS

CAPACITY

- 1,000/1,500 lbs.

PLATFORM SIZES

- 24" wide x 36" long
- 24" wide x 48" long

BASE SIZES

- 17 1/2" wide x 36" long
- 17 1/2" wide x 48" long

TRAVEL

- 24" & 36"

LOWERED HEIGHT

- 9 1/4"

ELF Lifts - see chart for above measurements

SAFETY

- Velocity fuse on all cylinders
- Upper limit by pass on ELF lifts

POWER SUPPLIES

Foot Pump - manually powers lifts, foot release for controlled lowering.

Hand release on ELF lifts

D/C Battery

Hand Held Pendant c/w built-in 12 volt 6 amp charger

MAINTENANCE

- Hinged top for easy access to power unit and cylinders
- Self lubricated bushings on all pivot points

OPTIONS

- Oversized platforms
- Rotating tops
- Bellow safety skirting

ELF 770 DOUBLE SCISSOR LIFT



ELF 330/660/1100/1650



ELF PORTABLE FOOT PUMP LIFTS MANUALLY POWERED SCISSOR LIFTS *Economical Portable Lifts*

MODEL NO.	CAPACITY (lbs.)	PLATFORM SIZE (W X L) (IN.)	LOW HT (IN.)	RAISED HT (IN.)	HANDLE HT (IN.)	WHEEL (DIAM.)	OVERALL SIZE (W X L) (IN.)	STROKES TO MAX. HT
ELF330	330	17.75 X 27.5	8.75	29.5	38	4	17.75 X 36	26
ELF660	660	19.75 X 32	11	35.5	39	5	19.75 X 42	25
ELF770	770	19.75 X 32	11.25	51.5	39	5	19.75 X 42	52
ELF1100	1100	19.75 X 35.75	13.5	35.5	38	5	19.75 X 42	38
ELF1650	1650	20 X 39.25	16.5	40	39	6	20 X 53	52



PORTABLE HAND PUMP LIFT

MODEL NO.	CAPACITY (LBS.)	STD. PLAT. BASE (W X L) (IN.)	LOW HT (IN.)	TRAVEL (IN.)	TOTAL HT (IN.)	STROKES TO MAX HT	WEIGHT (LBS)
PH24-6	660	19.675 X 32	10.62	24	34.5	1.5/stroke	200

PORTABLE FOOT PUMP - MANUALLY POWERED SCISSOR LIFTS

MODEL NO.	CAPACITY (lbs.)	STD. PLAT. BASE (W X L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	TRAVEL (IN.)	TOTAL HT (IN.)	OVERALL DIAM. (W X L X H) (IN.)	STROKES TO MAX HT	SHIP WEIGHT (LBS)
24" TRAVEL									
PF24-10	1,000	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	1"/stroke	265
PF24-15	1,500	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	1"/stroke	280
36" TRAVEL									
PF36-10	1,000	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	1"/stroke	295
PF36-15	1,500	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	1"/stroke	315



PORTABLE D/C BATTERY POWER - HAND CONTROL SCISSOR LIFTS

MODEL NO.	CAPACITY (lbs.)	STD. PLAT. BASE (W X L) (IN.)	OVERSIZED PLATFORMS (UP TO) (IN.)	LOW HT (IN.)	TRAVEL (IN.)	TOTAL HT (IN.)	OVERALL DIAM. (W X L X H) (IN.)	SPEED TO MAX HT	SHIP WEIGHT (LBS)
24" TRAVEL									
PB24-10	1,000	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	8 seconds	325
PB24-15	1,500	24 x 36	40 x 48	9 1/4	24	33	25 x 51 x 36	14 seconds	340
36" TRAVEL									
PB36-10	1,000	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	12 seconds	355
PB36-15	1,500	24 x 48	40 x 60	9 1/4	36	45	25 x 63 x 45	18 seconds	375

